

ØA Cup diameter	B Length over both cups (without circlips, excluding accessories)		SICIT CODE	O.E.M. CODE	ULT - U.Joint life torque capacity [Nm]	TFAT - Reversing dynamic/fat igue torque [Nm]	FT - Functional limit torque [Nm]	OFF.PRICE	%	PRICE DISCOUNTED	
65,0	157,0		I050	S225.5/SA	6.620	15.000	39.000	68	10	64	
65,0	157,0		I050/SKFW					69	10	66	
65,0	172,0		I065	587.48 / 687.65 / BR 77 / 100	6.840	15.000	39.000	66	10	66	
65,0	172,0		I065/SKFW					67	10	64	
72,0	185,0		I100	587.50 / BR 80	8.000	19.000	49.400	168	10	168	
74,0	217,0		I120	587.55 / BR 83	11.790	25.000	65.000	196	10	196	
74,0	185,0		I130		11.540	25.000	65.000	173	10	164	
74,0	195,0		I140	104 / 106	11.670	25.000	65.000	186	10	186	
74,0	179,9		I150	225.9-208.9	11.520	25.000	65.000	185	10	185	
74,0	171,0		I200	198.8	11.650	25.000	65.000	193	10	183	
83,0	190,0		I210		11.930	25.000	65.000	286	30	258	
83,0	195,0		I220	KEMPF SERIES 109	13.720	25.000	65.000	286	30	272	
83,0	217,0		I230		13.960	25.000	65.000	305	30	275	
83,0	220,0		I240	250.9 / 115	13.960	25.000	65.000	305	30	290	
83,0	231,4		I260	587.60 / BR 84	14.890	25.800	67.080	305	30	290	
83,0	179,9		I270	208.8	10.710	26.000	67.600	312	30	297	
95,0	216,0		I330		18.010	35.000	91.000	403	30	363	
95,0	219,0		I340	250.8	18.360	35.000	91.000	383	30	364	
95,0	250,0		I360	285.9 / 120 / 124	21.940	36.000	93.600	416	30	395	
110,0	245,0		I430		25.990	50.000	130.000	483	30	435	
110,0	251,5		I440		26.940	50.000	130.000	483	30	435	
110,0	243,5		I450	285.8	25.700	50.000	130.000	483	30	435	
110,0	275,0		I460	315.9 / 135 / 140	30.380	74.800	194.480	617	30	586	
130,0	266,5		I630	315.8	36.440	71.000	184.600	871	50	784	
130,0	269,0		I640	315.8	36.740	71.000	184.600	871	50	697	
130,0	302,0		I650	350.9 / 145	42.820	110.000	286.000	1.115	50	892	
145,0	299,0		I660		48.910	100.000	260.000	1.293	50	1.034	
145,0	294,3		I670	350.8	47.840	100.000	260.000	1.293	50	1.034	
145,0	336,5		I680	WT390.9	57.130	160.000	416.000	1.284	50	1.027	
145,0	342,0		I690	S390.8	58.520	160.000	416.000	1.284	50	1.027	
HEAVY DUTY UNIVERSAL JOINTS (Split yoke design) 4 grease nipples on cups or 4 plug screw on cups (unless cup Ø65-Ø120-Ø130) with 1 central grease nipple (CG) or 2 side grease nipple (2SG)											
65,0	143,0	220,0	CG	I065FL	190.50			191	10	181	
74,0	129,0	213,0	CG	I160FL	392.50 / 292.50			179	10	179	
74,0	154,0	238,0	CG	I180FL	190.55 / BR 82			179	10	179	
83,0	129,0	234,0	CG	I280FL	390.60	15.520	23.000	59.800	340	30	323
83,0	139,0	244,0	CG	I300FL	392.55 / 292.55 / BR 85	16.440	36.000	93.600	340	30	323
83,0	175,0	280,0	2SG	I320FL	190.60	19.760	17.000	44.200	365	30	347
95,0	139,0	261,0	CG	I380FL	390.65	23.050	36.000	93.600	437	30	415
95,0	160,0	282,0	CG	I400FL	392.60 / 292.60 / BR 90	26.060	53.000	137.800	452	30	430
95,0	190,0	312,0	2SG	I420FL	190.65	29.840	44.216	114.962	465	30	442
110,0	160,0	296,0	CG	I480FL	390.70	34.420	53.000	137.800	554	30	527
110,0	176,0	312,0	CG	I500FL	392.65 / 292.65 / BR 95	37.060	75.000	195.000	554	30	527
110,0	210,0	346,0	2SG	I520FL	190.70	42.670	75.000	195.000	808	30	768
120,0	235,0	377,0	2SG	I540FL	190.75	54.320	71.000	184.600	930	30	884
120,0	176,0	323,0	CG	I560FL	390.75	43.020	75.000	195.000	956	30	908
120,0	196,0	343,0	2SG	I580FL	392.70 / 292.70 / BR 97	47.460	102.000	265.200	946	30	851
130,0	196,0	362,0	CG	I600FL	390.80 / BR 98	62.380	102.000	265.200	1.310	30	1.244
130,0	216,0	377,0	CG	I620FL	393.75 / 292.75	66.040	116.000	301.600	1.310	30	1.179
130,0	262,0	423,0	CG	I700FL				2.498	30	2.248	
154,0	250,0	430,0	CG	I790FL	393.80	96.000	220.000	572.000	2.772	10	2.633
154,0	250,0	430,0	CG	I790.10FL	393.80	96.000	220.000	572.000	2.603	50	2.082